AMENDMENTS TO THE CLAIMS

There are no amendments to the claims, which stand as indicated in the following listing of claims:

Claim 1 (original). An optical scanning apparatus comprising:

a scanner body; and

a self-propelled light bar assembly supported within the scanner body.

Claim 2 (original). The optical scanning apparatus of claim 1, and further comprising a platen supported by the scanner body, and wherein the self-propelled light bar assembly comprises a drive wheel in contact with a drive track defined on the platen to allow the drive wheel to drive the light bar assembly along the platen.

Claim 3 (original). The optical scanning apparatus of claim 1, and further comprising a drive track supported within the scanner body, and wherein the self-propelled light bar assembly comprises a drive wheel in contact with the drive track to allow the drive wheel to propel the light bar assembly with respect to the scanner body.

Claim 4 (original). The optical scanning apparatus of claim 3, and further comprising a platen supported by the scanner body and having a first edge, and wherein the drive track is positioned adjacent to the first edge of the platen.

Claim 5 (original). The optical scanning apparatus of claim 3, and wherein the light bar assembly comprises a biasing member configured to urge the drive wheel towards the drive track.

Claim 6 (original). The optical scanning apparatus of claim 3, and wherein the light bar assembly is supported within the scanner body by the drive track.

Claim 7 (original). The optical scanning apparatus of claim 3, and wherein the drive wheel includes a rubberized outer portion, and the drive track has a non-smooth surface to allow the rubberized outer portion of the drive wheel to engage the drive track.

Claim 8 (canceled).

Claim 9 (original). The optical scanning apparatus of claim 1, and wherein the light bar assembly comprises a rotary electric motor configured to propel the light bar assembly.

Claim 10 (original). The optical scanning apparatus of claim 1, and wherein the light bar assembly comprises a linear electric motor configured to propel the light bar assembly.

Claim 11 (previously presented). An optical scanning apparatus comprising:

- a scanner body;
- a light bar assembly supported within the scanner body, the light bar assembly comprising a drive motor and a light source, the light bar assembly configured to move the drive motor and the light source together.

Claim 12 (original). The optical scanning apparatus of claim 11, and wherein the scanner body defines an inside upper surface, and wherein the drive wheel contacts the inside upper surface of the scanner body.

Claim 13 (original). The optical scanning apparatus of claim 12, and further comprising a support surface within the scanner body, upon which the light bar assembly is supported, and wherein the light bar assembly further comprises support wheels which rest on the support surface.

Claim 14 (original). The optical scanning apparatus of claim 13, and wherein the light bar assembly further comprises biasing members which support the support wheels on the light bar assembly, and wherein the biasing members urge the support wheels against the support surface, and thereby urge the drive wheel against the drive surface.

Claim 15 (original). The optical scanning apparatus of claim 11, and further comprising a position detecting system to allow the detection of the position of the light bar assembly with respect to the scanner body.

23

24

25

Claim 16 (original). An optical scanning apparatus comprising:

a scanner body;

a magnet-track portion of a linear electric motor fixedly supported within the scanner body;

a light bar assembly comprising a slider portion of a linear electric motor; and wherein the light bar assembly is supported in the scanner body to place the magnet-track portion in proximity to the slider portion to thereby allow the light bar assembly to be driven along the magnet-track portion.

Claim 17 (original). The optical scanning apparatus of claim 16, and wherein the light bar assembly is suspended from the magnet-track portion.

Claim 18 (original). The optical scanning apparatus of claim 16, and wherein the light bar assembly rests on top of the magnet-track portion.

Claim 19 (original). The optical scanning apparatus of claim 16, and wherein the light bar assembly rests on a support surface defined within the scanner body such that the slider-portion and the magnetic-track portions are not in direct contact with one another.

Claim 20 (original). The optical scanning apparatus of claim 16, and further comprising a position detecting system to allow the detection of the position of the light bar assembly with respect to the scanner body.

Claim 21 (original). The optical scanning apparatus of claim 20, and wherein the position detecting system comprises:

a linear encoding strip supported within the scanner body and mounted parallel to the magnet-track portion; and

a sensor supported by the light bar assembly and configured to detected the linear encoding strip.

20

21

22

24

23

25

Claim 22 (original). The optical scanning apparatus of claim 16, and wherein:

the light bar assembly is defined by a first end and a second end;

the magnet-track portion is a first magnet-track portion, the slider portion is a first slider portion, and the slider portion is supported proximate the first end of the light bar assembly;

the optical scanning apparatus further comprising:

- a second magnet-track portion supported within the scanner body; and
- a second slider portion supported proximate the second end of the light bar assembly and in contact with the second magnet track portion.

Claim 23 (original). A method of moving a light bar assembly within a scanner body of an optical scanning apparatus comprising:

providing a stationary track within the scanner body; providing a motive source supported by the light bar assembly; and moving the light bar assembly along the stationary track using the motive source.

Claim 24 (original). The method of claim 23, and wherein the light bar assembly is moved to a plurality of positions along the stationary track, the method further comprising determining the position of the light bar assembly as it is moved along the stationary track.

Claim 25 (original). The method of claim 23, and further comprising urging the light bar assembly against the stationary track while moving the light bar assembly along the stationary track.

Claims 26-28 (canceled).

Claim 29 (previously presented). A scanner, comprising:

- a light configured to move linearly within the scanner;
- a motor in fixed association with the light source such that the light source and the motor are moved together.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25

Claim 30 (previously presented). The scanner of claim 29, further comprising a support member, the light and the motor fixedly attached to the support member, the support member movable within the scanner.

Claim 31 (previously presented). The scanner of claim 30, wherein the motor is configured to linearly move the support member within the scanner.

Claim 32 (previously presented). The scanner of claim 30, wherein the motor is connected to a drive wheel via a series of meshing gears, the drive wheel contacting a track within the scanner, the drive wheel carried by the support member.

-- End of Amendments to the Claims --